

# The DRIVE® PTV Gas Specifications

## DIMENSIONS

<b>OVERALL LENGTH</b>	94.3 in. (2395 mm)
<b>OVERALL WIDTH</b>	47.2 in. (1200 mm)
<b>OVERALL HEIGHT (with suntop)</b>	70.4 in. (1789 mm)
<b>OVERALL HEIGHT (without suntop)</b>	46.9 in. (1190 mm)
<b>WHEELBASE</b>	64.6 in. (1640 mm)
<b>FRONT WHEEL TREAD</b>	34.3 in. (870 mm)
<b>REAR WHEEL TREAD</b>	38.6 in. (980 mm)
<b>MINIMUM GROUND</b>	4.3 in. (110 mm)

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental  
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

**CLEARANCE**

**ENGINE/DRIVE TRAIN**

<b>ENGINE TYPE</b>	Yamaha built, low emission single cylinder 60° incline OHV
<b>DISPLACEMENT</b>	357 cm <sup>3</sup>
<b>BORE x STROKE</b>	85 x 63 mm
<b>HORSEPOWER</b>	11.4 HP (8.5 Kw/3500 rpm)
<b>COMPRESSION RATIO</b>	8.1:1
<b>LUBRICATION SYSTEM</b>	Splash style positive oil lubrication
<b>OIL CAPACITY</b>	1 U.S. quart (1 liter, 1000 cc)
<b>AIR CLEANER</b>	Two stage, urethane-foam pre-cleaner and high-capacity pleated paper cartridge

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental  
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

**COOLING SYSTEM**      Forced air

---

**CARBURETOR**      Mikuni BV26-18

---

**IGNITION SYSTEM**      Transistor magneto ignition

---

**TRANAXLE**      EnduraDrive™ V-belt automatic forward/reverse transaxle equipped with high-precision helical gears, 11.40:1 drive axle ratio

---

## **CHASSIS**

**FRAME**      HybriCore™ Chassis features a robotically welded automotive ladder-style frame mated to a polypropylene structural floor. Frame is protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatically applied polyester/urethane powder topcoat

---

**BODY**      Custom-formulated thermoplastic olefin, painted with a two-part topcoat of high-luster automotive grade polyurethane

---

**STEERING**      Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed bearings and greaseless tie-rod ends

---

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental  
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

**FRONT  
SUSPENSION** Tru-Trak II™ fully independent automotive-style strut suspension

---

**REAR SUSPENSION** Unit swing arm with coil springs over hydraulic shock absorbers

---

**BRAKES** Maintenance-free internal transaxle disc brake

---

**SEATING** Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a warp and moisture resistant polypropylene bottom, strengthened with plated steel inserts

---

**BUMPERS** Front and rear 5 mph energy-absorbing bumpers

---

**PERFORMANCE**

**MAX FORWARD  
SPEED** 15 mph (24 km/h)

---

**MAX REVERSE  
SPEED** 10 mph (16 km/h)

---

**TURNING RADIUS** 9.2 ft (2.8 m)

---

## **GENERAL**

<b>DRY WEIGHT (less battery)</b>	562 lbs (255 kg)
----------------------------------	------------------

---

<b>FUEL TANK CAPACITY</b>	6.3 US gal (24.0 L)
---------------------------	---------------------

---

<b>TIRE SIZE</b>	18.00 x 8.50-8.00 (4-ply rating)
------------------	----------------------------------

---

<b>SEATING CAPACITY</b>	2 persons
-------------------------	-----------

---

<b>AVAILABLE PAINT COLORS</b>	Glacier, Emerald, Garnet, Sandstone Metallic, Cobalt Metallic, Anthracite Metallic, Onyx Metallic
-------------------------------	---

---

<b>AVAILABLE SEAT &amp; SUNTOP COLOR</b>	Stone
--	-------

## **WARRANTY**

---

<b>Warranty</b>	Standard 4-year limited vehicle warranty
-----------------	--

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental  
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

\*Specifications subject to change without notice

---