

The DRIVE® Gas Specifications

DIMENSIONS

OVERALL LENGTH	94.3 in. (2395 mm)
-----------------------	--------------------

OVERALL WIDTH	47.2 in. (1200 mm)
----------------------	--------------------

OVERALL HEIGHT (with suntop)	70.4 in. (1789 mm)
---	--------------------

OVERALL HEIGHT (without suntop)	46.9 in. (1190 mm)
--	--------------------

WHEELBASE	64.6 in. (1640 mm)
------------------	--------------------

FRONT WHEEL TREAD	34.3 in. (870 mm)
------------------------------	-------------------

REAR WHEEL TREAD	38.6 in. (980 mm)
-----------------------------	-------------------

MINIMUM GROUND	4.3 in. (110 mm)
-----------------------	------------------

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

CLEARANCE

ENGINE/DRIVE TRAIN

ENGINE TYPE	Yamaha built, low emission single cylinder 60° incline OHV
DISPLACEMENT	357 cm ³
BORE x STROKE	85 x 63 mm
HORSEPOWER	11.4 HP (8.5 Kw/3500 rpm)
COMPRESSION RATIO	8.1:1
LUBRICATION SYSTEM	Splash style positive oil lubrication
OIL CAPACITY	1 U.S. quart (1 liter, 1000 cc)
AIR CLEANER	Two stage, urethane-foam pre-cleaner and high-capacity pleated paper cartridge

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

COOLING SYSTEM Forced air

CARBURETOR Mikuni BV26-18

IGNITION SYSTEM Transistor magneto ignition

TRANSAXLE EnduraDrive™ V-belt automatic forward/reverse transaxle equipped with high-precision helical gears, 11.40:1 drive axle ratio

CHASSIS

FRAME HybriCore™ Chassis features a robotically welded automotive ladder-style frame mated to a polypropylene structural floor. Frame is protected with a multi-step full-immersion phosphate treatment, electro-deposition epoxy-based coating, and an electrostatically applied polyester/urethane powder topcoat

BODY Custom-formulated thermoplastic olefin, painted with a two-part topcoat of high-luster automotive grade polyurethane

STEERING Self-compensating double reduction helical rack-and-pinion, permanently lubricated with sealed bearings and greaseless tie-rod ends

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

**FRONT
SUSPENSION** Tru-Trak II™ fully independent automotive-style strut suspension

REAR SUSPENSION Unit swing arm with coil springs over hydraulic shock absorbers

BRAKES Maintenance-free internal transaxle disc brake

SEATING Seamless, fabric-backed vinyl bonded to pure, virgin foam contoured seat cushions and mated to a warp and moisture resistant polypropylene bottom, strengthened with plated steel inserts

BUMPERS Front and rear 5 mph energy-absorbing bumpers

PERFORMANCE

**MAX FORWARD
SPEED** 15 mph (24 km/h)

**MAX REVERSE
SPEED** 11.4 mph (18.4 km/h)

TURNING RADIUS 9.2 ft (2.8 m)

GENERAL

DRY WEIGHT (less battery)	562 lbs (255 kg)
----------------------------------	------------------

FUEL TANK CAPACITY	6.3 US gal (24.0 L)
---------------------------	---------------------

TIRE SIZE	18.00 x 8.50-8.00 (4-ply rating)
------------------	----------------------------------

SEATING CAPACITY	2 persons
-------------------------	-----------

AVAILABLE PAINT COLORS	Glacier, Emerald, Garnet, Sandstone Metallic, Cobalt Metallic, Anthracite Metallic, Onyx Metallic
-------------------------------	---

AVAILABLE SEAT & SUNTOP COLOR	Stone
--	-------

WARRANTY

Warranty	Standard 4-year limited vehicle warranty
-----------------	--

**Yamaha Golf Carts & Utility – New / Used Sales, Service, Rental
Serving Minnesota, Wisconsin, North Dakota and South Dakota.**

*Specifications subject to change without notice
